



EPS-MATERIALS 1400 NORTH STATE STREET MARENGO, IL 60152

p: 800.618.4111 f: 815.568.4155 www.eps-materials.com

## PRODUCTS DESIGNED FOR THE ARCHITECTURAL MARKET

# Interior / Exterior Applications

Product	Polymer NVM	pH	MFFT (°C)	Coalescing Solvent (on binder nvm)	Description
<b>PRIMERS</b>					
EPS 2533	45.5	7.0 - 8.0	9	5 - 6% Texanol	Excellent adhesion, ink and tannin stain-blocking, early water resistance and corrosion resistance. Ideal for use as a universal primer or low gloss topcoat on ferrous and non-ferrous metal, cementitious, wood and plastic substrates. A great low VOC waterborne alternative to solvent-based primers.
<b>WALL &amp; HOUSE PAINTS - GLOSS</b>					
EPS 2721	48.0	7.5 - 8.5	15	10% Texanol	Self-crosslinking all-acrylic emulsion for VOC compliant high gloss applications. EPS 2721 offers excellent gloss development, early high temperature block resistance, stain resistance and adhesion for high performance gloss enamels.

rev. 09/09

**Questions? Call EPS Technical Service @ 1-800-601-8111**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.