



## Cementitious Substrates

### Polymers for Concrete Admixtures

Product	NVM	MFFT °C	Tg °C	Properties	Applications
EPS 2708	50.0	20	10	<ul style="list-style-type: none"><li>• Excellent adhesion and bond strength</li><li>• Reduces permeability of cement matrices</li><li>• Excellent water and UV resistance</li><li>• All-acrylic polymer</li><li>• Excellent high temperature pot life</li><li>• Improves flow of cement based systems</li></ul>	<ul style="list-style-type: none"><li>• ASTM C-1059-91 Standard Specification for Latex Bonding Agents</li><li>• Binder/Primer over cementitious substrates</li></ul>

rev. 09/24/09

**Questions? Call EPS Technical Service @ 1-800-601-8111**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.