



# Urethane Resins for Wood Flooring & Clear Finishes

## HIGH SOLIDS OIL MODIFIED URETHANES

PRODUCT	NVM	WPG	OIL TYPE	SOLVENT	ACID #	VISC.	VISC. Reduced	COLOR	Sward Hardness	NOTES
<b>EPS 4854</b>	70.0%	7.87	Mixed	LAMS/A100	2 Max.	S-U	N/A	6 Max.	25	<ul style="list-style-type: none"> <li>Improved thru dry and hardness development</li> <li>Low viscosity</li> <li>High gloss thru flat</li> <li><i>Ethyl Benzene non-reportable</i></li> </ul>
<b>EPS 4843</b>	80.0%	7.93	Soya	LAMS/A100	3 Max.	Z-Z3	F-H @ 65%	5 Max.	14	<ul style="list-style-type: none"> <li>Good hardness</li> <li>Good abrasion resistance</li> <li>Moderate dry</li> <li><i>Ethyl Benzene non-reportable</i></li> </ul>

LAMS = Low Aromatic (<1%), Rule 66, Mineral Spirits; HFMS = High Flash Mineral Spirits

Questions? Call EPS Technical Service @ 1-800-601-8111

rev 03-01-2011

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.