



Resins for Wood Flooring & Clear Finishes

LONG OIL ALKYDS FOR STAINS & URETHANE BLEND VEHICLES

PRODUCT	NVM	WPG	OIL TYPE	SOLVENT	ACID #	VISC	VISC. Reduced	COLOR	NOTES
EPS 6603*	70.0%	8.00	Soya	LAMS /Xylene	5 to 10	Z ₂ -Z ₄	U-W @ 60%	3 to 6	Excellent flow & leveling, fast dry, durability
EPS 6677	100.0%	8.30	Linseed	None	10 Max.	W-Y		10 Max.	Excellent flow & leveling, wood penetration, solvent free
EPS 6848	96.25%	8.30	Soya	A100	5 to 10	Z ₂ -Z ₃ +½	G-I @ 70%	12 Max.	Excellent flow & leveling, low VOC <i>Ethyl Benzene non-reportable</i>

* For an ethyl benzene non-reportable version, consider EPS 6607

Questions? Call EPS Technical Service @ 1-800-601-8111

rev 10/09

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.