



# Urethane Resins for Wood Flooring & Clear Finishes

## POLYURETHANE DISPERSION FOR WOOD

PRODUCT	NVM	pH	SOLVENT	VOC	PROPERTIES	APPLICATIONS
EPS 4213	33.0%	7.7-8.3	Water/NMP/TEA	205 g/l	<ul style="list-style-type: none"><li>• Oxidizing polyurethane dispersion</li><li>• Chemical &amp; abrasion resistance</li><li>• No co-solvent or driers required</li><li>• Warm appearance on wood</li></ul>	<ul style="list-style-type: none"><li>• Wood Floor Coating</li></ul>

Questions? Call EPS Technical Service @ 1-800-601-8111

rev 10//09

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.