

EPS[®] 2127D All-Acrylic Emulsion

MARKET SEGMENT: ADHESIVES

COMMON APPLICATIONS: PRESSURE SENSITIVE ADHESIVES

EPS[®] 2127D is a high solids acrylic copolymer emulsion for label pressure sensitive adhesive applications. This polymer exhibits an excellent balance of adhesive properties and can be used in both tackified and non-tackified adhesive formulations.

PERFORMANCE BENEFITS

- Excellent balance of adhesive properties
- Clarity
- Yellowing resistance
- Low foaming
- Made without APEO surfactants

TYPICAL PROPERTIES

Weight Solids	60.0 ± 0.7%
Weight/Gallon	8.45 ± 0.10
рН	8.0 - 9.0
Volume Solids	59.4 ± 0.7%
Тд	-45° C

These typical properties do not represent specifications.

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epscca.com. 4/10/2024

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at https://www.epscca.com/galleries/pdfs/salesterms.pdf.